

Operating Humidity	10 % -- 85 %	10 % -- 85 %	10 % -- 85 %	10 % -- 85 %	10 % -- 85 %	10 % -- 85 %
Vertical	30	30	30	90	90	90
Standard	VESA Compilant (100 mm x 100	VESA Compilant (100 mm x	VESA Compilant (100 mm x 100	VESA Compilant (100 mm x	VESA Compilant (100 mm x	VESA Compilant (100 mm x
Glass	Strengthen Glass (for none- NW: 3.7KG GW:5.5KG	Strengthen Glass (for none- NW:4.5KG GW: 6.5KG	Strengthen Glass (for none-touch	Strengthen Glass (for none-	Strengthen Glass (for none-	Strengthen Glass (for none-
	LIYITEC/ Wan Da Five-Wire	LIYITEC/ Wan Da Five-Wire	15 Inches TFT Panel, XGA (1024	Powered with EETI resistive	Powered with Elo resistive	Powered with Elo resistive
	,Touchscreen sealed t	sealed t	Support VGA video input	Grade A Industrial grade LCD	Grade A Industrial grade LCD	Grade A Industrial grade
	gloved hands	hands	Multilingual OSD Menu	W all mount Vesa mounting	W all mount Vesa mounting	W all mount Vesa mounting
	Multiple mounting options	Multiple mounting options	With strong glass on top	Various interfaces combination	Ip 54 ; W aterproof / Dust	Ip 54 ; W aterproof / Dust
			With VESA mounting holes at the	Fanless Al metal construction.	various interfaces	various interfaces
	On screen display controls on	On screen display controls on	With strong base, with optional	Optioanl second display and	Fanless Al metal	Fanless Al metal
			Powered with Elo resistive touch		2-GB memory	2-GB memory

Address: Purok 3 Sitio Sampaguita St. Lamac Consolacion, Cebu 6001
Contact no: 032-4174521/ 09163560563
Email & Skype: 8startechnologies@gmail.com
Website: www.8startechnologies.weebly.com

Ask for BESTPRICE and If other vendors will offer a lower price, please inform us and we will drop our prices further! As of **September 6, 2016** - (Prices subject to change without prior notice)